



## Ecogear WMX

**Saturated ester based biodegradable lubricant for gearboxes in windmills**

### Description

Ecogear WMX is a premium synthetic biodegradable gear oil designed to provide exceptional anti-wear/extreme pressure (AW/EP) protection and corrosion control under the most adverse conditions. The product is specially formulated for lubricating wind turbine gearboxes for effective operation and long service life. It has a high viscosity index that minimizes changes in viscosity at elevated temperatures, while ensuring good low temperature fluidity of the lubricant for cold temperature operation. It also offers good micropitting resistance and high scuffing load.

Due to its saturated ester base biodegradable composition it is environmental friendly and good for use in sensitive areas such as at open sea.

### Benefits

- Protects against micropitting and scuffing of gear teeth and provides extended bearing life under extreme conditions
- Withstands oxidative and thermal breakdown at elevated temperatures to increase time between drain intervals, saving time and labor
- High quality synthetic base stocks with high VI ensure good lubricant film thickness over a broad temperature range
- Low temperature fluidity ensures smooth cold temperature starts
- Resists rust and corrosion
- Excellent air release properties
- Excellent compatibility with seals and coatings

### Typical performance data

	WMX 320
Density @ 15 °C kg/m <sup>3</sup>	1.01
Viscosity @ 40 °C, cSt	320
Viscosity @ 100 °C, cSt	37-38
Viscosity index	145
Pour point, °C	-33
Flash point, °C	270
Rust procedure ISO 7120	pass
Rust procedure salt water ISO 7120	pass
FZG micropitting FVA 54/7 at 90°C	>10
FZG scuffing test DIN ISO 14635-1	>12
FE-8 DIN 51819-3 weight roller loss	<5 mg
Copper corrosion ISO 2160 (3 hrs at 100°C)	1a

All performance data on this Technical Data Sheet are indicative only and can vary during production

**Matrix Specialty Lubricants BV - [info@matrix-lubricants.com](mailto:info@matrix-lubricants.com) - [www.matrix-lubricants.com](http://www.matrix-lubricants.com)**