

Foodmax[®] GREASE CAS SPRAYABLE HIGH TEMPERATURE HIGH PERFORMANCE FOODGRADE GREASE

Product Code 598221 Food Grade Spraycans

TECHNICAL DATA SHEET



Sprayable High Temperature High Performance Foodgrade Grease

This product is a fully synthetic food grade spray grease based on calcium sulphonate. This technology is characterized by exceptional mechanical stability, high dropping point, high load carrying performance, reduced wear and excellent resistance to water and steam and corrosion. This technology equals and in many ways outperforms any other spray grease.

Foodmax Grease CAS Spray is H-1 approved for use in food processing equipment where incidental contact with food may occur. They are designed to provide superior performance at low and elevated temperatures (from -40 up to over 200 °C) and during periods of infrequent lubrication in food processing applications. It is best suited for low to medium applications under adverse conditions including the combined action of (salt) water, steam, temperature and other foreign material such as process fluids which are seen in sugar beet processing. Foodmax Grease CAS can be used for general lubrication, slide ways, chains and high load bearings in the food industry.

Foodmax Grease CAS has excellent EP and AW properties. It contains no colorant and is formulated for enhanced resistance to hot, cold and salt water for superior rust protection.



e 400ml

Typical Performance Data

Typical	Value
Colour	Brown
Base oil type	PAO
Dropping point, °C	>300
Rust test	Passes
Salt fog corrosion, 1 mil d.f.t., hours	>300
Copper corrosion, rating	1b

All performance data on this Technical Data Sheet are indicative only and can vary during production.

+ 31 (0) 316 740 850 info@matrix-lubricants.com www.matrix-lubricants.com **ISO ISO** 9001;2015 21469;2006