

Performance[®] ANTI RUST L

LONG TERM CORROSION PROTECTION

Product Code
593516
Industrial Spraycans



CORROSION PROTECTION

Long Term Corrosion Protection

This product protects ferrous and non-ferrous parts during shipment and storage (both indoor & outdoor). As a result of the dewatering properties Performance Anti Rust L is very suitable for the protection of parts which have been in contact with metalworking emulsions and or water. After drying Performance Anti Rust L leaves an oil-waxy, light amber film with excellent anti-rust properties. Performance Anti Rust L is the best inhibitor for use as temporary coating. Performance Anti Rust can be removed by alkaline or solvent based degreasers.

This product can be used for wire ropes, electrical connections/wiring, sheltered coating, gear protectant/lubricant, cylinders, working/moving parts.

Extends tool life for metalworking operations, excellent outdoor protection, compatible with mineral oils, displaces water, great affinity for metallic surfaces, does not attack paint, plastic and rubbers, aerosol jet spray for pinpoint accuracy.



e 400ml

Typical Performance Data

Typical	Value
Film type	Greasy
Dewatering	Yes
Salt fog test, hours	72
Indoor protection, months	18-24
Outdoor protection, months	6-12
Drying time @ 20°C, min	30-50
Film thickness, micron	7,5
VOC	High

All performance data on this Technical Data Sheet are indicative only and can vary during production.