

# Performance<sup>®</sup> ALU-ZINC SPRAY

BRIGHT COLORED ZINC PROTECTION COATING SPRAY

Product Code  
826193

Industrial Sprayscans



PAINT

## Bright Colored Zinc Protection Coating Spray

This product is a high quality Alu-Zinc spray to treat galvanized and untreated steel. Performance Alu-Zinc Spray is used as a rust and corrosion protection on iron and steel surfaces.

Performance Alu-Zinc spray can be used for repair of damaged galvanic surfaces, protection of exhaust systems and protection of welding seams.

Resistant to petrol, chemicals and weather influences and has outstanding cathodic corrosion prevention. The spray has excellent adhesion, good filling properties and has a lighter color because of the aluminum component in this formula. It is spot-weldable and resists temperatures up to 250°C.



e 400ml

### Typical Performance Data

Typical	Value
Base	Epoxy-Ester
Colour	Silver-Grey
VOC, % w/w	76
Solid content, % w/w	24
Coverage, m <sub>2</sub>	1.25 to 1.75
Dust dry	10 to 15 min
Tack free	20 to 30 min
Hardened/Re-sprayable	>24h
Heat resistant	Up to 250°C

### How to use:

The surface should be clean, dry and free of grease and oil. The aerosol should have room temperature. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter. Apply the Alu-Zinc spray in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

All performance data on this Technical Data Sheet are indicative only and can vary during production.